

## HydroSub 60 Ancillary Equipment.

### HFS Flood Pump

Powered by the hydraulic lines that normally are connected to the submersible pump. Quick-connect couplings needed on the submersible pump and hydraulic lines.

Capacity: 20.000 ltr/min @ 0,3 bar

15.000 ltr/min @ 0,9 bar

10.000 ltr/min @ 1,4 bar

5.000 ltr/min @ 1.8 bar

Dead pressure 2.1 bar (21 mtr. lift)

#### Operating example:

At 5 meter lift, with 20 meter of 12" hose, a flow of 16.000 ltr/min can be achieved.

Material:

- Pump housing Aluminum
- Impeller Bronze
- Weight: approx. 130 kg
- Outlet 10" HFS Multi Lug coupling
- Powered by: HydroSub 60

Including:

- 4x10 mtr 12" flooding hose
- 1 connection hose 10" to 12".
- PVC coated polyester fabric, hydrolysis resistant

Weight approx. 1,5 kg/mtr

\* The HFS Flood Pump may also be used with the HFS 150, were the capacity allows 3 HFS Flood Pumps to be driven from a single HFS150, giving an incredible 45,000 ltrs/min pumping out capacity.



Eagle Business Services  
13901204064

老鹰电子技术开发有限公司  
电话: 010 84713253



# EAGLE

serving those that serve

Tel: +86 (10) 84713253. Fax: +86 (10) 84714294. Mobile: +86 13901204064.

Email: matrixsecurity@vip.sina.com Web: www.safetyeagle.com